



- 1 Advanced Filtration:
 - 3-Stage HEPA filtration
 - Meets OSHA silica rule requirements
 - 99+% filter efficiency
 - Switch-operated reverse pulse filter cleaning system
 - Longopac format allows for near-continuous use without dust exposure
- 2 2 motors provide strong pickup
- 3 Efficient size for big machine performance
- 4 Non-marking over-sized rear wheels
- 5 16-foot 3" hose

PRODUCT DESCRIPTION

Designed for full isolation of work debris, the DC400L is an excellent choice for dust containment on wood and concrete projects. The HEPA-level triple filtration and longopac bagging system meet the requirements of the OSHA silica dust rule (29 CFR 1926.1153) for concrete floor polishing. Dual motor suction provides powerful pick-up in an efficiently sized machine.

RECOMMENDED PRODUCTS



The Epoch HD is a 230V dual speed, multi-purpose machine with the muscle to handle the toughest floor jobs.



The Hydrashine driver and diamond disk system is a cost effective solution for polishing concrete floors.



CLS TopShield is a high performance micro-film forming surface treatment that hardens and protects concrete.



TECHNICAL DATA

Electrical Motor	2
Volts / Amps	115V, 20a
Hose	16.4 ft (5 m) of 3" hose
Power Cable length	10 ft (3 m)
CFM	212
Degree of separation, fine filter, EN 60335-2-69, Class M (%)	99.9%
Degree of separation, machine, EN 60335-2-69, Appendix A-A, Class H (%)	99.995%
Size	53.5 in x 22 in x 27 in
Machine Weight	110 lbs.
Warranty	Machine: Parts & Labor - 1 yr* *Excludes consumable wear items

Specifications are subject to change without notice.

AVAILABLE MODELS

07242A – DC400L Dust Containment System

