



Seal Coat

Waterborne Primer



MADE IN SWEDEN



CERAMIC SILICA

Ceramic Silica is one of the most durable, abundant minerals in the Earth's crust. Our ceramic fortification process allow us to create better, stronger and more durable finishes. Arboritec finishes penetrate deeper into the floor and are chemically bonded to the surface, enhancing the adhesion, strength and scratch resistance

KNOOP MINERAL HARDNESS TEST VALUES

DIAMOND	8000-8500
Arboritec's advanced fortifying mineral	
CERAMIC	4500-4600
The primary fortifying mineral used on prefinished floors	
ALUMINIUM OXIDE	1800-2200

PLEASE READ ALL INSTRUCTIONS AND SAFETY DATA SHEET BEFORE USING



PRODUCT DESCRIPTION

Arboritec™ Seal Coat is an 1 - component waterborne primer for indoor wood and parquet floors as well as on untreated cork. Seal Coat is NMP free, dries fast, reduces the side bonding effect and the fiber rising. Easy to sand, non-yellowing. It our most transparent primer. It is the perfect foundation for our waterborne finishes. For indoor use only.

DIRECTION FOR USE

The surface has to be sanded to a professional standard, dry and free from contamination. Moisture content of the wood should be max 15%. Protect the floor from direct sunlight and keep off all underfloor heating from day before application till 24 hours after application. Final sanding of the floor should be done with sanding paper 120 grit belt or 100 grit screen. The temperature of the floor, Seal Coat primer and air must be between 13°C (55°F) and 25°C (77°F). Relative humidity of the room should be between 40% and 60%. Higher humidity of room extends drying time of primer thus waiting time between layers will be longer. At high temperatures and low relative humidity add 2% Arboritec "Extender". Shake the container before use for 30-60 seconds. Allow it to rest for 2-3 minutes before applying. Do not dilute the primer.

APPLICATION

Application of the primer should be carried out along the direction of parquet strips and wood. Prevent direct sunshine on the floor during coating. If possible, do not apply the primer cross the direction of daylight. Windows/doors must be closed to prevent air flow and ventilation should be shut down for the time of application. Seal Coat is suitable for application with a lightweight t bar applicator, roller or brush. Only use roller for worn-out old flooring and floors with joints Always test the product on a smaller area to ensure colour and adhesion. Recommended method of application with a 10mm roller: in one layer 95-131g/m². Apply sufficient amount of product in order to ensure good levelling of roller/ applicator marks. Ready for intermediate sanding between 60-90 minutes after application.

TECHNICAL DATA

Base material	Waterborne acrylic dispersion
Recommended Use	As a primer before overcoating with Arboritec waterborne finishes.
Additional features	NMP free
VOC	This product contains max. 87g /l (EU limit value for this product (cat. A/i): 140 g/l (2010) 2004/42/CE)
Solids by volume	Approx. 35%
pH	Approx. 7
Approx. Weight/ Density	Approx. 1 035 kg/m ³ ; 8,64 lb/gal (US); 10,37 lb/gal (UK)
Odour	Very light, non-offending
Safety/Toxicity	Non-hazardous / Not classified
Coverage	400 – 500 sq. ft. per gallon with T-bar / 8-11 m ² / l or 95-131g/m ² with roller
Flow and leveling	Exceptional
Color	Wet: milky white, clear when dry
Drying time	20°C/ 68°F (RH 50%) 60-90 min.
Packaging	1 gallon (3,78 L)
Storage and transport	1 year from date of manufacture in unopened original container at 41F (5°C) to 77F (25°C). Keep from freezing!
Shelf life	See expiration date on canister.
Chemical resistance	Resistant to grease, water and ordinary household cleaners and detergents
Cleaning of tools	Thoroughly clean all application tools with water, right after using.
Disposal	Never pour surplus finish down the drains. Dispose it in accordance to local regulations.
Maintenance	To keep the floor looking its best, clean and maintain floor using Arboritec "Cleaner Spray" and "Refresher", following application instructions. Do not clean the floor before it is fully cured.

Safety data sheet is available for download at www.arboritec.com

For technical advice: Contact your distributor or

Arboritec AB technical service at +46 303 56330

Arboritec USA Inc. technical service at +1 877 4165972

Arboritec AB

Olof Wiksväg 9

44465 Jörlanda, Sweden

+46 303 56330

Arboritec USA Inc.

8400 E. Crescent Parkway, Suite 600

Greenwood Village, CO 80111, USA

+1 303 773 7143

Issued by ARBORITEC AB, Olof Wiksväg 9, 44465 Jörlanda, Sweden

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers' remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use. The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Arboritec can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product. This data sheet replaces all previous versions.